

# New Jersey Semi-Conductor Products, Inc.

20 STERN AVE.  
SPRINGFIELD, NEW JERSEY 07081  
U.S.A.

TELEPHONE: (973) 376-2922  
(212) 227-6005  
FAX: (973) 376-8960

## 1N48 GOLD BONDED GERMANIUM DIODE

### FEATURES

Low forward voltage drop—low power consumption  
Thirty years of proven reliability—one million hours mean time between failures (MTBF)  
Very low noise level  
Metallurgically bonded


### ABSOLUTE MAXIMUM RATINGS (at 25 °C, unless otherwise specified)

|                             |                  |
|-----------------------------|------------------|
| Peak Inverse Voltage        | 85 Volts         |
| Peak Forward Current        | 500 mA           |
| Operating Temperature Range | - 65 °C to 85 °C |
| Average Power Dissipation   | 80 mW            |

### ELECTRICAL CHARACTERISTICS

|                      | Symbol         | Conditions | Min | Max | Unit | T °C  |
|----------------------|----------------|------------|-----|-----|------|-------|
| Peak Inverse Voltage | PIV            | 1 mA       | 85  |     | V    | 25 °C |
| Reverse Current      | I <sub>r</sub> | 50 V       |     | 833 | μA   | 25 °C |
| Forward Voltage      | V <sub>f</sub> | 4 mA       |     | 1   | V    | 25 °C |

### MECHANICAL



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

